

GLX Series

Active & Passive Speaker

Active



GLX-15A



GLX-15



Introduction of features:

The GLX series are built by rugged and ultra-light gas-injected polypropylene enclosure.

This elaborately design enclosure effectively avoid the forming of standing wave.

The high quality woofer features high power and low distortion, the compression driver is made by a 44mm PEEK diaphragm. GLX series deliver clear, smooth sound. Its outstanding sound capability can be maximum performed under high dynamic condition. The high efficiency "CLASS-D" amplifier adopts switching mode power of wide-range voltage from 100V-240V, which make GLX much lighter than the "CLASS-D" amplifier but getting the equal sound. GLX is equipped with three handles, which is more convenient for carry.

The GLX is designed for meeting room, multi-function hall, music hall, hotel, coffee bar, mosque etc.

Features:

- >High efficiency "CLASS-D" amplifier, high power, low distortion, excellent sound quality.
- >Constant directivity horn for even coverage.
- >Rugged and ultra-light gas-injected polypropylene enclosure
- >EQ BOOST to optimize the frequency response, compressor limit LED indication, over heat LED indication.
- >Multi-angle cabinet design make GLX can be used for stage monitor.

Features:

Model	GLX-15	GLX-15A
Type	15" 2-way Active Speaker	15" 2-way Passive Speaker
Frequency Response	45Hz~20kHz(-10dB)	45Hz~20kHz(-10dB)
Sensitivity(1W@1m)	99dB	0dBu
Power Handling(RMS)	900W	800W
Coverage (H*V)	90°*60°	90°*60°
Crossover	1.8kHz	-----
Nominal Impedance	8Ω	-----
LF	1*15" Woofer	1*15" Woofer
HF	1*44mm HF compression driver	1*44mm HF compression driver
Max. SPL	131dB	127dB
Input Connector/Output Connector	2*SPEAKON	Combo(XLR / JACK),XLR
Dimension (W * H * D)	45*37*71	45*37*71
Net Weight	19 Kg	19.5 Kg
Rated Voltage	-----	AC 110 /230V,50-60Hz