

PS Series

Active & Passive Speaker

PS-215
PS-215A



Active



Passive



PS-15
PS-15A



Active



Passive



Introduction of features:

PS series of professional engineering box using high precision acoustic instrument precision debugging, make its beautiful tone, voice thick, powerful dynamics; after the appearance with elaborate design can reflect more designers have great originality, mellow soft corner feeling letting a person from the appearance to the essence of the design will be able to. PS series of products using high-quality electrical components, high pitched more with over-current protection circuit design, can effectively improve the reliability and stability of the speaker voice. PS series can be made of various flexible appearance match to satisfy different occasions to product requirements. Can be used in conference rooms, multi-function hall, school and so on many occasions of speech reinforcement.

Features:

Model	PS-15	PS-15A	PS-215	PS-215A
Type	15" 2-way Passive	15" 2-way Active	2*15" 2-way Passive	2*15" 2-way Active
Frequency Response	45Hz~20kHz(-10dB)	45Hz~20kHz(-10dB)	45Hz~20kHz(-10dB)	45Hz~20kHz(-10dB)
Sensitivity(1W@1m)	95dB	0dBu	100dB	0dB
Power Handling(RMS)	800W	800W	1200W	1000W
Coverage (H*V)	90°*60°	90°*60°	90°*60°	90°*60°
Crossover	2.2kHz	2.2kHz	2.2kHz	2.2kHz
Nominal Impedance	8Ω	-----	4Ω	-----
LF	1*15" Woofer	1*15" Woofer	2*15" Woofer	2*15" Woofer
HF	1*44mm HF compression driver	1*44mm HF compression driver	1*44mm HF compression driver	1*44mm HF compression driver
Max. SPL	130dB	130dB	135dB	135dB
Input Connector/Output Connector	2*SPEAKON	TRS,TRS	2*SPEAKON	TRS,TRS
Dimension (W * H * D)	47.5*43*74	47.5*43*74	45*108*37	45*108*37
Net Weight	16.5 Kg	21 Kg	32 Kg	38 Kg
Rated Voltage	-----	AC 110 /230V	-----	AC 110 /230V