

CS Series

Ceiling Speaker

CS-22



CS-22

Type: One way
Power (RMS): 5W/10W
Impedance: 8 ohms
Line Voltage: 70V/100V AC
Frequency: 90-16KHz
Sensitivity (1w/1m): 90dB
Speaker (woofer): 5"
Cutout Dimensions: Ming loaded
Overall Dimensions: 180 * 70mm
Color: White

CS-33



CS-33 Waterproof

Type: One way
Power (RMS): 3W/6W
Impedance: 8 ohms
Line Voltage: 70V/100V AC
Frequency: 95-15KHz
Sensitivity (1w/1m): 88dB
Speaker (woofer): 3"
Cutout Dimensions: 100mm
Overall Dimensions: 120 * 80mm
Color: White

CS-35



CS-35

Type: One way
Power (RMS): 3W/6W
Impedance: 8 ohms
Line Voltage: 70V/100V AC
Frequency: 80-18KHz
Sensitivity (1w/1m): 90dB
Speaker (woofer): 5"
Cutout Dimensions: 150mm
Overall Dimensions: 185 * 58mm
Color: White

CS-36



CS-36

Type: One way
Power (RMS): 5W/10W
Impedance: 8 ohms
Line Voltage: 70V/100V AC
Frequency: 90-16KHz
Sensitivity (1w/1m): 91dB
Speaker (woofer): 6"
Cutout Dimensions: 165mm
Overall Dimensions: 190 * 70mm
Color: White, Black

