

# ZC2018

# Clamp Meter



**6000 Counts**



- Standard Accessories**
1. 2 x Battery
  2. 2 x Test lead
  3. 1 x Standard user manual
  4. 1 x Thermocouple probe
  5. 1 x Black soft case

Specifications	Range	Accuracy
DC Voltage	600.0mV/6.000V/60.00V/600.0V/1000V	±(0.5%+3)
AC Voltage	600.0mV/6.000V/60.00V/600.0V/750V	±(1.0%+3)
DC Current	600.0μA/6000μA	±(1.2%+3)
AC Current	600.0μA/6000μA	±(1.5%+3)
	600.0A/1000A	±(2.0%+30)
Resistance	600.0Ω/6.000kΩ/60.00kΩ/600.0kΩ/6.000MΩ	±(0.5%+3)
	60.00MΩ	±(1.5%+3)
Capacitance	9.999nF	±(5.0%+20)
	99.99nF/999.9nF/9.999μF/99.99μF/999.9μF	±(2.0%+5)
	9.999mF	±(5.0%+5)
Frequency	99.99Hz/999.9Hz/9.999kHz/99.99kHz/ 999.9kHz/9.999MHz	±(0.1%+2)
Duty Cycle	1%-99%	±(0.1%+2)
Temperature	-20°C~1000°C/-4°F~1832°F	±(2.5%+5)
Diode/Continuity	●/●	

### Features

Auto/Manual ranging	True RMS	Data hold
Backlight	Low battery alert	Auto power off

### General

Power Supply	2 x 1.5V AA Battery
Dimension	240*90*45mm
Weight	323g