

ZC-B900

Smart Clamp Meter



6000 Counts

- Standard Accessories**
1. 2 x Battery
 2. 2 x Test leads
 3. 1 x Standard user manual
 4. 1 x Black soft case
 5. 1 x Thermocouple probe

Specifications	Range	Accuracy
DC Voltage	6.000V/60.00V/600.0V	±(0.5%+3)
AC Voltage	6.000V/60.00V/600.0V	±(1.0%+3)
DC Current	60.00A/600.0A	±(2.0%+30)
AC Current	60.00A/600.0A	±(2.0%+30)
Resistance	6.000kΩ	±(1.5%+3)
	60.00kΩ/600.0kΩ/6.000MΩ	±(0.5%+3)
	60.00MΩ	±(1.5%+3)
Capacitance	6.000nF	±(5.0%+20)
	60.00nF/600.0nF/6.000μF/60.00μF/600.0μF	±(2.0%+5)
	6mF/60.000mF	±(5.0%+5)
Frequency	6.000Hz/60.00Hz/600.0Hz/6kHz/60kHz/600kHz/6MHz/10MHz	±(0.5%+5)
Temperature	-30°C~1000°C/-22°F~1832°F	
Diode/Continuity	●/●	

Features		
Auto ranging	True RMS	Data hold
Backlight/Flashlight	Low battery alert	Auto power off
Inrush current	Peak Hold	Smart mode
DC & AC current test		

General	
Power Supply	2 x 1.5V AAA Battery
Dimension	172*64*32mm
Weight	161g