

# DX Series

## Active & Passive Speaker



**Active**

**Passive**

**DX-150  
DX-150A**

**DX-120  
DX-120A**

**DX-80  
DX-80A**

### Introducon of features:

DX series has been called as economic speaker which is more popular among our clients because of its multifunctioning usages from one side and its lower price from other side.

This type of plastic speaker, mostly owning of a modern design, looking good to be applied in many places, it owns an acceptable perfect sound quality accordance with its D class amplifier.

DX series offers a pleasant options for customers such as, USB, Bluetooth, microphone inputs, radio, recorder, extra band output and etc.

Model	DX-80	DX-80A	DX-120	DX-120A	DX-150	DX-150A
Type	8" 2-way Passive	8" 2-way Active	12" 2-way Passive	12" 2-way Active	15" 2-way Passive	15" 2-way Active
Frequency Response	75Hz~20kHz(-10dB)	75Hz~20kHz(-10dB)	50Hz~20kHz(-10dB)	50Hz~20kHz(-10dB)	45Hz~20kHz(-10dB)	45Hz~20kHz(-10dB)
Sensitivity(1W@1m)	92dB	92dB	96 dB	96 dB	97dB	97dB
Power Handling(RMS)	350W	300W	500W	400W	700W	500W
Coverage (HxV)	90°x40°	90°x40°	90°x60°	90°x60°	90°x60°	90°x60°
Crossover	2.7kHz	2.7kHz	2.3kHz	2.3kHz	2.2kHz	2.2kHz
Nominal Impedance	8Ω	-----	8Ω	-----	8Ω	-----
LF	1x8" Woofer	1x8" Woofer	1x12" Woofer	1x12" Woofer	1x15" Woofer	1x15" Woofer
HF	1x25mm	1x25mm	1x25mm	1x25mm	1x34mm	1x34mm
Max. SPL	117dB	117dB	124dB	124dB	128dB	128dB
Input Connector/Output	2xSPEAKON	TRS,TRS	2xSPEAKON	TRS,TRS	2xSPEAKON	TRS,TRS
Connector						
Dimension (W x H x D)			40x60x33.5	40x60x33.5	45.5x71x39.5	45.5x71x39.5
Net Weight	20 Kg	20 Kg	12 Kg	14.5 Kg	16 Kg	20 Kg
Rated Voltage	-----	AC 100 /240V	-----	AC 100 /240V	-----	AC 100 /240V