

VX Series

Active & Passive Speaker



VX-80A



VX-100A



VX-120A



VX-150A

Introduction of Features:

This unit is radio-interference suppressed. This appliance meets the requirements of the current European and national guidelines. Conformity has been established and the relevant statements and documents have been deposited by the manufacturer:

- Balanced MIC + LINE inputs with level
- Balanced LINE output
- Treble + Bass controls + Master volume
- LINE output and speaker out (except VX-80A)
- MP3-PLAYER (FM/SD/USB) with bluetooth
- Mobile App Controller
- Heavy duty Polypropylene cabinet housing
- Active 2-way crossover
- Perfect for both permanent installations and portable use (Rental, DJ, ...)



Specification:

Model	VX-150A	VX-120A	VX-100A	VX-80A
Type	15" 2-way Active	12" 2-way Active	10" 2-way Active	8" 2-way Active
Frequency Response	45Hz-18KHz	50Hz-18KHz	55Hz-18KHz	60Hz-18KHz
Sensitivity(1W@1m)	97dB	96 dB	95dB	92dB
Power Handling(RMS)	600W	500W	400W	300W
Coverage (HxV)	90° x 60°	90° x 60°	90° x 60°	90° x 40°
Crossover	2.2kHz	2.3kHz	2.3kHz	2.7kHz
Nominal Impedance	-----	-----	-----	-----
LF	1 x 15" Woofer	1 x 12" Woofer	1 x 10" Woofer	1 x 8" Woofer
HF	1 x 44mm	1 x 34mm	1 x 10mm	1 x 10mm
Max. SPL	128dB	124dB	120dB	117dB
Input Connector/Output Connector	XLR, TRS / XLR, TRS	XLR, TRS / XLR, TRS	XLR, TRS / XLR, TRS	TRS, RCA / RCA
Dimension (W x H x D)	479 x 402 x 685mm	408 x 343 x 585mm	338 x 280 x 505mm	269 x 234 x 410mm
Net Weight	19 Kg	14.5 Kg	10 Kg	8 Kg
Rated Voltage	AC 100 /240V	AC 100 /240V	AC 100 /240V	AC 100 /240V