

C Series

Catridge



C-3500

C-3000

C-2500

C-2200

C-2000

C-1200

Features:

C-3500

Impedance: 600Ω
Sensitivity: -52(±3) dB (at 1 KHz) (0dB=1V/Pa)
Frequency response: 50 Hz ~15 KHz
Pattern: Unidirectional
Weight: 40g

C-3000

Impedance: 600Ω
Sensitivity: -49(±3) dB (at 1 KHz) (0dB=1V/Pa)
Frequency response: 60 Hz ~13 KHz
Pattern: Unidirectional
Weight: 44g

C-2500

Impedance: 600Ω
Sensitivity: -50(±3) dB (at 1 KHz) (0dB=1V/Pa)
Frequency response: 50 Hz ~13 KHz
Pattern: Unidirectional
Weight: 57g

C-2200

Impedance: 600Ω
Sensitivity: -51(±3) dB (at 1 KHz) (0dB=1V/Pa)
Frequency response: 60 Hz ~16 KHz
Pattern: Unidirectional
Weight: 51g

C-2000

Impedance: 600Ω
Sensitivity: -51(±3) dB (at 1 KHz) (0dB=1V/Pa)
Frequency response: 60 Hz ~16 KHz
Pattern: Unidirectional
Weight: 51g

C-1200

Impedance: 600Ω
Sensitivity: -52(±3) dB (at 1 KHz) (0dB=1V/Pa)
Frequency response: 50 Hz ~15 KHz
Pattern: Unidirectional
Weight: 44g